



SIN 350

Issue 1.5

April 2015

Suppliers' Information Note

For The BT Network

BT Public Switched Telephone Network (PSTN): Network Tones And Announcements

Each SIN is the copyright of British Telecommunications plc. Reproduction of the SIN is permitted only in its entirety, to disseminate information on the BT Network within your organisation. You must not edit or amend any SIN or reproduce extracts. You must not remove BT trade marks, notices, headings or copyright markings.

This document does not form a part of any contract with BT customers or suppliers.

Users of this document should not rely solely on the information in this document, but should carry out their own tests to satisfy themselves that terminal equipment will work with the BT network.

BT reserves the right to amend or replace any or all of the information in this document.

BT shall have no liability in contract, tort or otherwise for any loss or damage, howsoever arising from use of, or reliance upon, the information in this document by any person.

Due to technological limitations a very small percentage of customer interfaces may not comply with some of the individual characteristics which may be defined in this document.

Publication of this Suppliers' Information Note does not give or imply any licence to any intellectual property rights belonging to British Telecommunications plc or others. It is your sole responsibility to obtain any licences, permissions or consents which may be necessary if you choose to act on the information supplied in the SIN.

This SIN is available in Portable Document Format (pdf) from: <http://www.btplc.com/sinet/>

Enquiries relating to this document should be directed to: help@sinet.bt.com

CONTENTS

1	SCOPE	3
2	NETWORK SUPERVISORY TONES.....	3
3	NETWORK ANNOUNCEMENTS	5
4	GLOSSARY	5
5	HISTORY	6

1 Scope

This document describes the supervisory tones generated by the BT network and gives general information about BT network announcements. Tones and announcements encountered on the BT network can originate from other networks and from customer premises equipment. These tones and announcements are not covered by this Suppliers' Information Note (SIN).

In cases where the Network Termination Equipment (NTE) is mains powered, the conditions quoted in this SIN apply when mains power is being applied to the NTE. The conditions applicable when mains power is removed from the NTE may be different to those quoted in this SIN.

Much of the information contained in this SIN has been published previously in documents such as British Standards.

Changes to the network that affect the correct working of approved terminal equipment will be published in BT SINs, available from <http://www.btplc.com/sinet/>. If the changes impact on the content of this document then it will be updated.

This document was first published as BT Technical Interface Guide 8.

2 Network Supervisory Tones

The supervisory tones that will be returned from the BT network are listed in Table 1.

Table 1. Network Supervisory Tones

Network Generated Tone	Significance	Range of levels received at BT network interface	Tone Composition ($\pm 5\%$ except where stated)	Cadence ($\pm 10\%$ except where stated)
Proceed Indication <i>(Dial Tone)</i>	Proceed to dial indication	0 dBm to -27 dBm. Each tone separately 3 dB lower	350 Hz plus 440 Hz	Both tones continuous
Special Proceed Indication <i>(Interrupted Dial Tone)</i>	Proceed to dial indication when certain supplementary services have been invoked	0 dBm to -27 dBm. Each tone separately 3 dB lower	350 Hz plus 440 Hz	350 Hz tone - 0.75 s ON, 0.75 s OFF plus 440 Hz tone - continuous or both tones pulsed at the above rate.
Number Busy Tone <i>(Engaged Tone)</i>	Called Customer's line in use	0 dBm to -37 dBm.	400 Hz	0.375 s ON, 0.375 s OFF.

Network Generated Tone	Significance	Range of levels received at BT network interface	Tone Composition (± 5% except where stated)	Cadence (± 10 % except where stated)
Congestion Tone <i>(Path Engaged Tone)</i>	Routeing equipment is temporarily unavailable	-6 dBm to -43 dBm. 0 dBm to -37 dBm.	400 Hz	0.4 s ON, 0.35 s OFF, 0.225 s ON, 0.525 s OFF. Note: The shorter tone is 6 dBm higher than the longer tone.
Special Congestion Tone	Precedes some congestion announcements	0 dBm to -37 dBm.	400 Hz 1004 Hz	400 Hz tone - 0.2 s 1004 Hz tone - 0.3 s
Connection Not Admitted Indication <i>(Number Unobtainable Tone)</i>	Call cannot be routed to requested number	0 dBm to -37 dBm.	400 Hz	Continuous
Awaiting Answer Indication <i>(Ringing Tone)</i>	Implies that called Customers line is being rung	0 dBm to -37 dBm.	400 Hz + 450 Hz	0.4 s ON, 0.2 s OFF, 0.4 s ON, 2.0 s OFF. or 0.35 s ON, 0.22 s OFF. Then start at any point in 0.4 s ON, 0.2 s OFF, 0.4 s ON, 2 s OFF. Note: Cadence does not necessarily coincide with call arrival indication cadence.
Special Information Tone	Precedes certain announcements	0 dBm to -37 dBm.	950 Hz ± 50 Hz 1400 Hz ± 50 Hz 1800 Hz ± 50 Hz	Each frequency is sent for 330 ms ± 70 ms in the order given and with silent periods of up to 30 ms between adjacent signals.
Call Waiting Indication	Indicates a second incoming call	0 dBm to -37 dBm.	400 Hz	0.1 s ON, 2 - 5 s OFF.
Special Call Waiting Indication	Indicates a special second incoming call	0 dBm to -37 dBm.	400 Hz	0.03s ON, 0.01s OFF, 0.03s ON, 6.0s OFF.
Confirmation Tone	Used in some exchanges in place of an announcement to indicate that an interrogated service is active	0 dBm to -37 dBm.	1400 Hz	20 s followed by silence.

Network Generated Tone	Significance	Range of levels received at BT network interface	Tone Composition (± 5% except where stated)	Cadence (± 10 % except where stated)
Switching Tone	Used in some exchanges in place of an announcement to indicate that an interrogated service is not active	0 dBm to -37 dBm.	400 Hz	0.2 s ON, 0.4 s OFF, 2.0 s ON, 0.4 s OFF.

3 Network Announcements

A variety of announcements may be returned to a user during call set-up and clear down. Other announcements may be returned to the user during set-up, operation and cancellation of supplementary services and services other than basic access to the Public Switched Telephone Network (PSTN) (e.g. Chargecard, 0345, 0800, 0898)

Some announcements will be preceded by Special Information Tone.

All announcements will have a mean level at the BT network interface in the range -14 dBm to -28 dBm and will be repeated for between 1 and 5 cycles.

4 Glossary

BT	British Telecommunications plc
NTE	Network Termination Equipment
PSTN	Public Switched Telephone Network
SIN	Suppliers' Information Note
TIG	Technical Interface Guide

5 History

TIG 8 Issue 1	October 1998	First Issued as TIG 8.
Issue 1.0	February 2000	Document re-issued as SIN 350 with editorial changes.
Issue 1.1	May 2002	Description of 'Acknowledgement Tone' removed as not a PSTN derived tone. Document format updated to current SIN style.
Issue 1.2	July 2004	Interrupted Dial Tone added as an alternative name for Special Proceed Indication.
Issue 1.3	July 2005	Cadence for Special Call Waiting Indication corrected.
Issue 1.4	April 2014	Content review and editorial changes. Change SINet site references from http://www.sinet.bt.com to http://www.btplc.com/sinet/
Issue 1.5	April 2015	In table 1, reference to payphone (pay tone) has been removed

-END-