

ERRATA SHEET

86B-Types
Data Selective
Calling System Stations

1. Page 3 - Left Column - Second Paragraph
Add an "*" following the word "device" at end of the third sentence.
Add the following at the bottom of the page:
"* The DC2 used to cut on an auxiliary receiving device, and the DC4 or ETX used to cut it off must be followed, in each case, by a DELETE character to provide timing."
2. Page 9 - Left Column - Sec. 4.2 - Sixth Line of First Paragraph
Add an "*" following the word "progress".
Add the following at the bottom of the page:
"* An erroneous polling response may be produced if polling is initiated when selected receiving stations are in the roll-call state, i.e., if the computer switcher has sent the ETX of the message but has not yet sent the EOT that causes selected receivers to go to the "idle" state at the conclusion of a delivery. (See Section 4.11 - Roll-Call Operation and Responses.) To avoid this, polling should not be performed during the interval between the ETX and the EOT."
3. Page 15 - Right Column - Sec. 4.10 - Next to Last Line
Change to read:
"... switcher send the three-character sequence DC2 EOT DC2 before..."
4. Page 18 - Left Column - Next to Last Line
Change last word to read "generate."
5. Page 18 - Right Column - Sec. 4.11 - First Paragraph
Add an "*" following the word "it" at the end of the paragraph.
Add the following at the bottom of the page:
"* If the roll-call feature is not employed and the system includes 86B1 ROTR terminals as receiving stations (rather than only as auxiliary receivers), the message delivery should be concluded with the two-character sequence ENQ EOT, rather than with EOT alone. This is necessary to trigger tape feedout at the ROTR stations."